




## BNP 600 & 720 Mini Blast Rooms - Suction System



Model BNP-720 with 900 CFM Reclaimer and Reverse Pulse Collector

**Clean  
Peen  
Deburr  
Finish**



Cutaway shown

**BNP 600 & 720 Mini Blast Rooms deliver efficient, affordable media blasting to clean, peen, deburr, or finish parts.**

### Common Applications

- Remove rust, mill scale, heat scale, and carbon buildup from metals
- Strip paint, powder coating, plating, and anodizing from parts for rework
- Eliminate burrs, parting lines, flashings, and other defects from castings and injection-molded parts
- Extract residual sand from castings
- Beautify steel, stainless steel, aluminum, brass and other metals with a uniform matte finish
- Etch artwork and lettering into glass, stone, plastics, metal and other materials
- Clean release agents and material buildup from molds

### BNP 600 & 720 Suction Cabinets Feature:

#### Safety

- ✓ Full-length, neoprene-on-fabric gloves resist wear and protect operator.
- ✓ Ceiling-mounted, four-tube fluorescent light fixture with abrasive resistant Lexan® cover for extraordinary visibility.
- ✓ Safety interlocks interrupt blasting if either door is opened. (Conforms to US regulations.)
- ✓ Heavy-duty, cam-style latch seals doors tight through years of service.

#### Productivity

- ✓ Unique Air Logic system (pilot actuated) to maximize air flow to the nozzle.
- ✓ Double-wall, sound-insulated doors.
- ✓ 12-gauge steel all-welded construction, with strength breaks to form a rigid, long-lasting cabinet shell.
- ✓ Large 20" X 30" view window.

#### Convenience

- ✓ Tilt-out window, for tool-free glass changes in minutes.
- ✓ Pressure regulator, gauge, and electric switch mounted within easy reach.
- ✓ Built-in blow-off gun helps keep dust inside the cabinet, not on your floor.

### BNP Blast Gun with Ceramic Nozzle

The BNP blast gun sets the industry standards for performance, versatility, and durability. The ergonomically proven grip reduces operator fatigue and increases productivity. The standard ceramic nozzle is perfect for bead blasting, while the optional tungsten or boron carbide nozzles stand up to hundreds of hours of blasting with today's aggressive abrasives.


### Popular Accessories

- Adjustable Vortex Tube (for lightweight media)
- Air-powered Vertical Lift Door
- Alox Kit
- Curtains (black or high-visibility white)
- HEPA filter (RP model only)
- Manometer Kit
- Oscillator Assembly
- Timed door release
- 30" and 48" Dia. Turntables
- Work Car & Track Assembly
- Additional operator station
- Additional door set

# S P E C I F I C A T I O N S

## COMPLETE SYSTEM

Actual space required depends on equipment configurations, options and desired work flow. Allow additional work space for operator and maintenance access.



<b>BNP600</b>	Model illustrated: BNP-600 with free-standing Reclaimer and RPH Dust Collector	<b>BNP720</b>
<b>A - 59" (1499mm)</b>		<b>A - 72" (1829mm)</b>
<b>B - 60" (1524mm)</b>		<b>B - 72.25" (1835mm)</b>
<b>C - 81.25" (2064mm)</b>		<b>C - 91.25" (2318mm)</b>

## CABINET

### Working Chamber Size


<b>BNP600</b>	<b>56" wide (1422 mm)</b>
	<b>58.5" deep (1486 mm)</b>
	<b>53" high (1346 mm)</b>
<b>BNP720</b>	<b>69" wide (1753 mm)</b>
	<b>70.5" deep (1778 mm)</b>
	<b>63" high (1600 mm)</b>

### Window Size (safety glass)

<b>30" wide (762 mm)</b>
<b>20" high (508 mm)</b>

Double swinging doors on right side only. Door interlock system conforms to U.S. government regulations.

### Door Opening



<b>BNP600</b>	<b>BNP720</b>
<b>A - 55.5" (1410 mm)</b>	<b>67" (1702 mm)</b>
<b>B - 47" (1194 mm)</b>	<b>58" (1473 mm)</b>
<b>C - 21.5" (546 mm)</b>	<b>22.5" (572 mm)</b>
<b>D - 27" (686 mm)</b>	<b>38" (965 mm)</b>
<b>E - 46" (1168 mm)</b>	<b>54" (1372 mm)</b>

## DUST COLLECTORS

Dry filters are suitable for most industrial applications where the dust collector can be shut off periodically to shake dust from the 100% cotton sateen filter tubes. Dry filters trap 98% of dust down to 1.0 micron.

Reverse pulse cartridge dust collectors (which trap 99.7% of dust down to 0.5 micron) allow non-stop, high-production blasting. The polyester-cellulose cartridges are automatically pulse cleaned for maximum filter efficiency. Worn cartridges can be replaced in minutes.

Dry Filters	Reverse Pulse Collector
5 sq ft filter area per tube 900 cfm DF has 40 tubes (200 sq ft)	235 sq ft filter area per cartridge RPC-2 has 2 cartridges (470 sq ft) RPH-3 has 3 cartridges (705 sq ft)

Clemco is committed to continuous product improvement. Specifications are subject to change without notice.

Clemco Industries is an ISO 9001 certified company.


## MEDIA RECLAIMER

### The Heart of ZERO's Blasting System

Our exclusive media reclaimers continuously extract dust and debris and return properly sized, usable media to the blast system. The standard reclaimer handles all non-metallic media. For metallic media, specify reduced ID conveying hose.

The suction blast metering valve is infinitely adjustable from fully-closed to wide open, and locks into any setting without tools.

The versatile design of our larger reclaimers lets you quickly adapt the system to your changing needs - add media hoppers, rubber liners, or pull-through dust-collection.



## BNP BLAST GUN

### AIR CONSUMPTION

SIZE	NOZZLE ORIFICE	AIR JET	CFM at 80 PSI	M <sup>3</sup> /Min at 5,5 BAR	MINIMUM RECLAIMER
No. 4	1/4"	1/8"	21	0,60	<b>900 CFM (25 m<sup>3</sup>/m)</b>
No. 5	5/16"	5/32"	32	0,90	<b>900 CFM (25 m<sup>3</sup>/m)</b>
No. 6	3/8"	3/16"	48	1,35	<b>900 CFM (25 m<sup>3</sup>/m)</b>
No. 7	7/16"	7/32"	62	1,76	<b>900 CFM (25 m<sup>3</sup>/m)</b>
No. 8	1/2"	1/4"	85	2,41	<b>900 CFM (25 m<sup>3</sup>/m)</b>

BNP Mini Blast Rooms are furnished with a No. 5 ceramic nozzle.

## ELECTRICAL

(Available with three phase motors only):

**900 CFM (25 m<sup>3</sup>/m)** 2HP, 3PH, 60HZ, (1.5KW, 220V, 3PH, 50HZ,);  
**1200 CFM (34 m<sup>3</sup>/m)** 5HP, 3PH, 60HZ, (3.7KW, 220V, 1PH, 50HZ,);

Other motors and electrical configurations are available to make your system compatible with local power systems.

## ORDERING INFORMATION

Model Number	Reclaim CFM (m <sup>3</sup> /m)	Dust Coll.	230V Stk. No.	460V Stk. No.	Ship Wt. lb(kg)
BNP-600-900 DF	900 (25)	Dry Filter	12667	12673	2,215 (1005)
BNP-600-900 RPC	900 (25)	RPC-2	12668	12674	2,495 (1132)
BNP-600-900 RPH	900 (25)	RPH-2	14394	14438	3,070 (1393)
BNP-600-1200 RPH	1200 (34)	RPH-3	14441	14442	3,825 (1735)
BNP-720-900 DF	900 (25)	Dry Filter	12652	12658	2,835 (1420)
BNP-720-900 RPC	900 (25)	RPC-2	12653	12659	3,115 (1286)
BNP-720-900 RPH	900 (25)	RPH-2	14396	14450	3,690 (1674)
BNP-720-1200 RPH	1200 (34)	RPH-3	14453	14454	4,735 (2148)

Distributed By: